

ChiliProject - Bug # 1106: LDAP On-the-fly user creation fails if mail is not set

Status:	Open	Priority:	Normal
Author:	Jan Härtel	Category:	
Created:	2012-08-01	Assignee:	
Updated:	2012-08-01	Due date:	
Remote issue URL:			
Affected version:			
Description:	On-the-fly user creation for LDAP users fails, if no mail address is set within LDAP for this user. In the ChiliProject the attribute "Email" is set to the correct LDAP field. The returned uninformative error message is: <pre><pre> Processing AccountController#login (for 10.10.4.51 at 2012-07-18 11:12:09) [POST] Parameters: {"action"=>"login", "authenticity_token"=>"oMiQHtR2CWYHCmy7vluLN/oTVg1Yt4PeRu8/6q0cys=", "password"=>"[FILTERED]", "username"=>"name", "controller"=>"account", "back_url"=>"http%3A%2F%2Ffea-tts%2F", "login"=>"Anmelden Å»"} **** Debugger requested, but was not available: Start server with --debugger to enable **** **** Debugger requested, but was not available: Start server with --debugger to enable **** TypeError (can't convert false into String): app/models/user.rb:140:in `try_to_login' app/controllers/account_controller.rb:143:in `password_authentication' app/controllers/account_controller.rb:138:in `authenticate_user' app/controllers/account_controller.rb:26:in `login' /usr/lib/ruby/1.8/phusion_passenger/rack/request_handler.rb:92:in `process_request' /usr/lib/ruby/1.8/phusion_passenger/abstract_request_handler.rb:207:in `main_loop' /usr/lib/ruby/1.8/phusion_passenger/railz/application_spawner.rb:418:in `start_request_handler' /usr/lib/ruby/1.8/phusion_passenger/railz/application_spawner.rb:358:in `handle_spawn_application' /usr/lib/ruby/1.8/phusion_passenger/utils.rb:184:in `safe_fork' /usr/lib/ruby/1.8/phusion_passenger/railz/application_spawner.rb:354:in `handle_spawn_application' /usr/lib/ruby/1.8/phusion_passenger/abstract_server.rb:352:in `__send__' /usr/lib/ruby/1.8/phusion_passenger/abstract_server.rb:352:in `main_loop' /usr/lib/ruby/1.8/phusion_passenger/abstract_server.rb:196:in `start_synchronously' /usr/lib/ruby/1.8/phusion_passenger/abstract_server.rb:163:in `start' /usr/lib/ruby/1.8/phusion_passenger/railz/application_spawner.rb:213:in `start' /usr/lib/ruby/1.8/phusion_passenger/spawn_manager.rb:262:in `spawn_rails_application' /usr/lib/ruby/1.8/phusion_passenger/abstract_server_collection.rb:126:in `lookup_or_add' /usr/lib/ruby/1.8/phusion_passenger/spawn_manager.rb:256:in `spawn_rails_application' /usr/lib/ruby/1.8/phusion_passenger/abstract_server_collection.rb:80:in `synchronize' /usr/lib/ruby/1.8/phusion_passenger/abstract_server_collection.rb:79:in `synchronize' /usr/lib/ruby/1.8/phusion_passenger/spawn_manager.rb:255:in `spawn_rails_application' /usr/lib/ruby/1.8/phusion_passenger/spawn_manager.rb:154:in `spawn_application' /usr/lib/ruby/1.8/phusion_passenger/spawn_manager.rb:287:in `handle_spawn_application' /usr/lib/ruby/1.8/phusion_passenger/abstract_server.rb:352:in `__send__' /usr/lib/ruby/1.8/phusion_passenger/abstract_server.rb:352:in `main_loop' /usr/lib/ruby/1.8/phusion_passenger/abstract_server.rb:196:in `start_synchronously' /usr/lib/ruby/1.8/phusion_passenger/passenger-spawn-server:61 Rendering /var/www/chiliproject3/public/500.html (500 Internal Server Error) </pre></pre> Correct behaviour should be to prompt the user for the missing information.		

Further information in the discussion: <https://www.chiliproject.org/boards/1/topics/1905>

This is produced with ChiliProject 3.3.0.080c5b63c (SQLite)

<pre>

Gems included by the bundle:

- * actionmailer (2.3.14)
- * actionpack (2.3.14)
- * activerecord (2.3.14)
- * activeresource (2.3.14)
- * activesupport (2.3.14)
- * acts-as-taggable-on (2.1.0)
- * bundler (1.0.21)
- * coderay (1.0.7)
- * fastercsv (1.5.5)
- * gravatarify (3.0.0)
- * i18n (0.4.2)
- * json (1.7.3)
- * liquid (2.3.0)
- * net-ldap (0.3.1)
- * rack (1.1.3)
- * rails (2.3.14)
- * rake (0.9.2.2)
- * rdoc (3.12)
- * ruby-openid (2.1.8)
- * rubytree (0.5.3)
- * sqlite3-ruby (1.2.5)
- * tzinfo (0.3.33)

</pre>

History